



Product description

TransferRite® Ultra™ 782U is a medium tack application tape featuring a premium, moisture resistant saturated paper backing. It also features a unique rubber-based adhesive system equiped with a special adhesive promotor that provides superior adhesion to liner. Especially designed for use on graphics where large areas of exposed liner are present.

Performance features

→ Easy application: superior adhesion to liner

ightarrow Terrific lay-flat: reduces wrinkling, tunneling and edge lifting

→ Premium paper: added dimensional stability and humidity resistance

→ Cost effective: trouble-free stacking and storage

→ Terrific Time-Saver: minimal handwork - little or no heat vacuum needed

Applications

Can be used for decals requiring long term storage and decals that need to be rolled and shipped. 782U is best used for decals from 5cm up to 31cm.

Technical information

Paper thickness (without adhesive)	110 μm
Adhesive thickness	24 μm
Total thickness	134 μm
Adhesive type	natural rubber latex with adhesive promotor
Adhesive strength (adhesion to steel)	3.6 N/25mm (medium tack)
Core colour	yellow
Tensile strength	92 N/25mm
Elongation at break	14%
Shelf life (from time of manufacture)	24 months (21°C / 50% humidity)

Important: The performance of all adhesive products is affected by many factors: heat, humidity, type of substrate, texture, inks used, and application technique. Our suggestions and recommendations concerning the use and application of our products are based on tests we believe are reliable. However, the purchaser must test the suitability of our products for his intended use under his own operating conditions. American BiltRitle Inc. Assumes no liability for claims beyond the replacement value of any defective products, and is no way for consequential or incidental damages. These products are not suitable for prolonged outdoor exposure.



Industriezone 23, B-9600 Ronse, Belgium tel: +32 (0)55/23.51.51 fax: +32 (0)55/23.51.61 e-mail: info@idealabi.com website: www.idealabi.com

