

792U



TransferRite
ULTRA™

Product description

TransferRite® Ultra™ 792U is a high tack application tape featuring a premium, moisture resistant saturated paper backing. It also features a unique rubber-based adhesive system equipped with a special adhesive promotor that provides superior adhesion to liner. Especially designed for use on graphics where large areas of exposed liner are present.

Performance features

- Easy application: superior adhesion to liner
- Terrific lay-flat: reduces wrinkling, tunneling and edge lifting
- Premium paper: added dimensional stability and humidity resistance
- Cost effective: trouble-free stacking and storage
- Terrific Time-Saver: minimal handwork - little or no heat vacuum needed

Applications

Can be used for decals requiring long term storage and decals that need to be rolled and shipped. 792U is best used for decals smaller than 5cm and fine line striping.

Technical information

Paper thickness (without adhesive)	110 µm
Adhesive thickness	24 µm
Total thickness	134 µm
Adhesive type	natural rubber latex with adhesive promotor
Adhesive strength (adhesion to steel)	4.4 N/25mm (high tack)
Core colour	red
Tensile strength	92 N/25mm
Elongation at break	14%
Shelf life (from time of manufacture)	24 months (21 °C / 50% humidity)

Important: The performance of all adhesive products is affected by many factors: heat, humidity, type of substrate, texture, inks used, and application technique. Our suggestions and recommendations concerning the use and application of our products are based on tests we believe are reliable. However, the purchaser must test the suitability of our products for his intended use under his own operating conditions. American BilRite Inc. Assumes no liability for claims beyond the replacement value of any defective products, and is no way for consequential or incidental damages. These products are not suitable for prolonged outdoor exposure.



AMERICAN BILRITE INC.
EXCELLENCE THROUGH QUALITY

Industriezone 23, B-9600 Ronse, Belgium
tel: +32 (0)55/23.51.51 fax: +32 (0)55/23.51.61
e-mail: info@idealabi.com website: www.idealabi.com

