

DTEC 810/812 Magnetic film

07/2016

Product Description

DTEC 810/812 Magnetic film is a premium flexible magnetic sheeting product. It has a welded white gloss or matt pvc vinyl face. The magnetic side has a UV hardened coating. Only the 0.9mm thickness is suitable for moving vehicle application.

Specifications	
Thickness	0.65 en 0.90mm
Facefilm	Matt or Gloss white PVC film (100μ)
Weight	0.65mm = 2.4 kg/m ² en 0.90mm = 3.3 kg/m ²
Roll Size	620mm x 10,0mtr and 1020mm x 10,0mtr
Printability	Screen, Solvent, UV and Offset inks
Magnetic properties	Pole width: 2.0mm Magnetic pull: 53 g/cm ² (semi-anisotropic)
Temperature range	- 30°C to + 55°C
Cutting	Knife-, Die-, Scissor cutting and slitting
Shelf Life	2 years when stored at 15 to 25°C and ± 50 % relative humidity (in original packaging)
Durability	The material is waterproof and can also be used for outdoor use – 2 years

Installation instructions

It is important to follow the installation instructions especially on magnetic carsigns. The magnetic sheets should be peeled away from the vehicle surface on a daily basis and cleaned. Failure to follow any of these instructions can cause damage to the sign and to the vehicle's paint finish and other surfaces.

Disclaimer

All technical data and advice is based on our experience and measured testing that we believe to be reliable. It remains the customer's responsibility to test our products suitability for the purpose intended. The quality of our products is regularly examined, upgraded and developed. We reserve the right, without prior notice, to adjust, upgrade and improve the chemical structures or physical characteristics of their products in accordance with their latest knowledge.