

Description

Cleaning and care products especially developed for maintenance of vehicles wrapped with matt car wrapping films from ORAFOL.

	Intensive cleaner – matt	Long lasting seal – matt
Description	Intensive cleaner with high degree of dirt and insect removal power for vehicles with matt car wrapping films. Gloss causing debris is removed gently and the matt effect is restored.	With this sealing product, matt car wrapping films are cleaned, cared for and preserved. Afterwards, contamination can be removed far easier. In addition, it gives a very good water repellent effect.
Application	Spray the vehicle from the bottom up and let it work for 1-2 minutes. Then rinse thoroughly using a strong water jet.	Spray onto the film surface in sections and wipe off with a soft microfiber cloth.
Notes	Do not apply onto hot coatings, films or rims, do not let it dry out. Before use check for material compatibility in a concealed area.	Shake well before use. Protect product from freezing!
Ingredients (according to regulation (EG) 648/2004	Nonionic surfactants less than 5%, cationic surfactants less than 5%, amphoteric surfactants less than 5%, phosphates less than 5 %, chelating agents (IDS) less than 5%, phosphonates less than 5%, preservatives (Methylisothiazolinone, Benzisothiazolinone), additional information: Emollients.	Nonionic surfactants less than 5%, fragrances (free of allergens 2003/15/EC), additional information: de-ionized water, brighteners, alcohol, glycol ether.
Shelf life	3 years*	3 years*
Application temperature	> 10° C, but not in direct sunlight, not on hot surfaces.	> 10° C, but not in direct sunlight, not on hot surfaces.

* in original packaging, at 0 – 35° C

Important to note

The above information is based upon our present knowledge and practical experience. The information is given without any guarantee or agreement with regards to the quality or properties of the material. It does not constitute a warranty of any certain quality, properties and/or service life concerning the ORAFOL® products.

Please note that by nature films are more sensitive than lacquers. Therefore, films must be treated and maintained with the greatest care. For application of ORAFOL colour films (wrapping and removal) as well as for maintenance and use, please refer to our documents 'Processing Guidelines' and 'Maintenance and Usage Terms' (both documents are available in pdf format to download: www.orafol.com/gp/europe/en/support). If our guidelines are not followed, please be advised that in particular the maximum service life information, stated as based on our experience, does not apply. Further information about the expected maximum service life is found in the Processing Guidelines (see no. 2 there). If the processing guidelines and maintenance and usage terms are not complied with, any warranty and liability is excluded.

Please contact a professional workshop or ORAFOL's customer support if you have further questions.

IMPORTANT NOTICE

All ORAFOL® products are subject to careful quality control throughout the manufacturing process and are warranted to be of merchantable quality and free from manufacturing defects. Published information concerning ORAFoL® products is based upon research which the Company believes to be reliable although such information does not constitute a warranty. Because of the variety of uses of ORAFoL® products and the continuing development of new applications, the purchaser should carefully consider the suitability and performance of the product for each intended use, and the purchaser shall assume all risks regarding such use. All specifications are subject to change without prior notice.

